Njordair CA-14 - constant air, 5-m module

Njordair CA-14 - 46-ft Inflatable Work Tent

Source: Manufacturer product page

Dimensions

Width, outside	**14 m (45'11")**
Width, inside	**12 m (39′4")**
Length	**5 m (16′5")**
Height, outside	**7.3 m (23′11")**
Height, inside	**6.1 m (20′)**
Packed Size	**2 x 1.5 x 1.5 m (6.5′ x 5′ x 5′)**
Tent-only weight	**402 kg (886 lbs) (tent only)**

Construction

Frame	**1 m (3'3") double wall + internal mesh air baffles**
Side Walls	**630 gsm PVC (flame retardant)**
End Walls	**2 x removable - 630 gsm PVC (flame retardant)**
Roof	**630 gsm PVC peaked roof (flame retardant)**
Module Connection	**9 x dutch lacing sections + rain cover**

Standard Features

Windows	**6 x clear PVC windows - 60 cm x 90 cm (23″ x 35″) (each end wall)**
Access	**Personnel access in removable end walls; machinery / equipment access**
Fans	**2 x 1.5 hp constant air (per module)**
Fill Points	**2 x internal + 2 x external**

Standard Features

Deflation Zips	**2 x 1 m (3'3″) quick deflate zips**
Internal Ties	**40 x webbing loops**
Document Pouch	**1 x A4 clear external pouch (each end wall)**
Duct Holes	**2 x 300 mm (12″) ducting holes with velcro flap**

Anchors (Each side)

High Level	**11 x multi directional webbing - 150 kg (330 lbs) capacity**
Mid Level	**7 x multi directional webbing - 150 kg (330 lbs) capacity**
Ground Level	**7 x heavy duty metal ring - 150 kg (330 lbs) capacity**

Anchors (Each end)

High Level	**6 x multi directional webbing - 150 kg (330 lbs) capacity**
Ground Level	**10 x multi directional webbing - 150 kg (330 lbs) capacity**

Standard Accessories

Transport Bag	**1 x PVC transport bag**
Repair Kit	**Included**
Stakes	**Reinforced steel, 18 mm (11/16") diameter**
Ties	**10 mm (3/8″) polypropylene rope**

Configuration

Model	**CA-14 Fast Tent**
Width class	**46 ft / 14 m**
Air system	**Constant air; continuous blower operation**
Module length	**5 m / 16 ft 5 in**

Configuration

Modularity	**Connectable modules with removable end walls**
Blower electrical supply	**110-V electric blower standard in manufacturer FAQ; local voltage/plug options by destination**