Njordair CA-6 - constant air, 5-m module

Njordair CA-6 - 20-ft Inflatable Work Tent

Source: Manufacturer product page

Dimensions

Width, outside	**6 m (19'8")**
Width, inside	**5.1 m (16'9")**
Length	**5 m (16'5")**
Height, outside	**3.4 m (11'2″)**
Height, inside	**2.7 m (8'10")**
Packed Size	**1.2 x 1 x 1 m (4′ x 3'3″ x 3'3″)**
Tent-only weight	**185 kg (408 lbs) (tent only)**

Construction

Frame	**45 cm (1'6") double wall + internal mesh air baffles**
Side Walls	**630 gsm PVC (flame retardant)**
End Walls	**2 x removable - 630 gsm PVC (flame retardant)**
Roof	**630 gsm PVC peaked roof (flame retardant)**
Module Connection	**9 x dutch lacing sections + rain cover**

Standard Features

Windows	**2 x clear PVC - 60cm x 90cm (23″ x 35″) (each end wall)**
Access	**Personnel access in removable end walls**
Fans	**1 x 1.5 hp constant air (per module)**
Fill Points	**2 x internal + 2 x external**
Deflation Zips	**2 x 1m (3'3″) deflation zips**

Standard Features

Internal Ties	**40 x webbing loops**
Document Pouch	**1 x A4 clear external pouch (each end wall)**
Duct Holes	**2 x 45 cm (1'6″) service duct holes with velcro flap (each end wall)**

Anchors (Each side)

High Level	**4 x multi directional webbing - 150 kg (330 lbs) capacity**
Mid Level	**4 x multi directional webbing - 150 kg (330 lbs) capacity**
Ground Level	**6 x heavy duty metal ring - 150 kg (330 lbs) capacity**

Anchors (Each end)

High Level	**n/a**
Ground Level	**4 x heavy duty, multi directional webbing - 150 kg (330 lbs) capacity**

Standard Accessories

Transport Bag	**1 x PVC Transport Bag**
Repair Kit	**Included**
Stakes	**Reinforced steel, 18 mm (11/16") diameter**
Ties	**18 mm (3/4″) polypropylene rope**

Configuration

Model	**CA-6 Fast Tent**
Width class	**20 ft / 6 m**
Air system	**Constant air; continuous blower operation**
Module length	**5 m / 16 ft 5 in**

Configuration

Modularity	**Connectable modules with removable end walls**
Blower electrical supply	**110-V electric blower standard in manufacturer FAQ; local voltage/plug options by destination**