# SAI Drive Solutions DURA-Drive Rental 15 HP / FR5 / 480 V 3-phase

SAI DURA-Drive 15-hp Mobile VFD Panel - 480 V

Source: Manufacturer product page

## Selected mobile configuration

| | |
|---|---|
| Package family | **SAI DURA-Drive Type 3R rental panel** |
| Published configuration | **15 hp / 11 kW; FR5** |
| Input supply | **480 V AC, three phase** |
| Published current rating | **23 A** |
| Duty basis | **Normal duty / low overload, variable torque** |
| Drive chassis | **Danfoss VACON NXP series** |
| Mounting | **Portable dolly** |

## Enclosure and controls

| | |
|---|---|
| Enclosure | **Type 3R; general outdoor rain protection** |
| Ambient operating range | **–10 degC to 40 degC / 14 degF to 104 degF** |
| Thermal control | **Thermostat-controlled fans and heating pads** |
| Operator interface | **LCD / keypad plus local controls and status indicators** |
| Remote control | **Prewired remote-command terminal block** |
| Connection access | **Separate input and motor junction boxes** |
| Security | **Padlock provisions and programmable passcodes** |
| Electrical protection | **Surge protection device** |

## Shipping reference

| | |
|---|---|
| Shipping dimensions | **62 x 26 x 27 in; H x W x D** |

## Shipping reference

| | |
|---|---|
| Approximate shipping weight | **220 lb** |
| Application matching | **Select by motor nameplate current and duty; constant-torque loads require sizing review** |