DEWALT DCF860B

DEWALT DCF860B 20V MAX XR 1/4 in quick-connect hex chuck Impact Driver

Source: Manufacturer product page

Drive & output

Exact selected model	**DCF860B**
Drive	**1/4 in quick-connect hex chuck**
Maximum fastening torque	**Up to 2,500 in-lb, high-speed mode**
No-load speed	**0-3,800 rpm**
Impact rate	**0-4,500 ipm**

Power & controls

Power source	**Cordless, DEWALT 20V MAX battery system**
Voltage	**20 V maximum initial; 18 V nominal**
Motor	**Brushless**
Selected configuration	**Tool only; battery and charger selected separately**
Trigger	**Variable speed with electronic brake**
Work lighting	**Nine built-in LED s; 20-minute worklight setting**

Modes & handling

Speed 1	**0-1,800 rpm forward; maximum 1,250 in-lb fastening**
Speed 2	**0-2,500 rpm forward; maximum 2,150 in-lb fastening**
Speed 3	**0-3,800 rpm forward; maximum 2,500 in-lb fastening**
Reverse speed	**0-3,800 rpm in all modes**
Asset management	**TOOL CONNECT chip-ready; optional chip purchased separately**

Dimensions

Length	**4.8 in (122.5 mm)**
Tool weight	**2.4 lb (1.1 kg)**