Milwaukee 2868-20

Milwaukee 2868-20 M18 FUEL 1-Inch D-Handle Impact Wrench

Source: Manufacturer product page

Drive & output

Exact selected model	**2868-20**
Drive	**1 in square, friction ring**
Form	**D-handle with standard anvil**
Maximum fastening torque	**Up to 1,900 ft-lb**
Maximum nut-busting torque	**Up to 2,000 ft-lb**
No-load speed	**0-1,200 rpm**
Impact rate	**0-1,440 ipm**

Power & controls

Voltage	**18 V DC**
Battery platform	**Milwaukee M18 rechargeable lithium-ion**
Battery compatibility	**All Milwaukee M18 battery packs**
Motor	**POWERSTATE brushless**
Electronic protection	**REDLINK PLUS overload, overheating and over-discharge protection**
Work lighting	**Tri- LED**
Handle	**360 deg adjustable and removable side handle**
Selected configuration	**Tool-only model; battery and charger are separate**
Recommended ambient operating temperature	**0-125 degF**
Connected tool functions	**ONE - KEY customization, tracking and management**

Model details

Weight	**21.5 lb, tool only**
Weight with heaviest compatible battery	**25 lb**
Control modes	**4-Mode DRIVE CONTROL**
Battery connection	**Patented vibration-isolating battery interface**