Guardian CR5 1400198 - 6 ft Class 1 Personal SRL

The Guardian CR5 1400198 is a six-foot single-leg personal self-retracting lifeline with webbing, an integrated shock pack and a steel snap hook. This Class 1 SRL-P connects at or above the dorsal D-ring and includes a swiveling top connection.

Guardian Fall Protection product family and configuration
Guardian CR5 Class 1 - Factory Instruction Manual Rev. D (PDF)
Guardian CR5 - Factory Technical Data Sheet Rev. C (PDF)

Manufacturer	Guardian Fall Protection
Model	CR5 / 1400198
Part number	1400198
Lifeline length	6 ft / 1.8 m
Configuration	Single-leg SRL-P
Classification	Class 1, ANSI Z359.14-2021
Anchorage position	At or above the harness dorsal D-ring; no free fall
Leading-edge use	Not permitted
Connector	Steel snap hook
ANSI user-weight range	130-310 lb / 59-140 kg, including clothing, tools and equipment
OSHA user-weight range	100-420 lb / 45-190 kg, including clothing, tools and equipment
Maximum arrest force	1,350 lb / 6 kN
Average arrest force	1,150 lb / 5.1 kN
Maximum arrest distance	3 ft / 0.9 m for the published 100-420 lb range
Minimum fall clearance	6.5 ft / 1.98 m in the factory baseline configuration; additional swing-fall and installation factors apply
Lifeline material / width	HMPE webbing, 1 in / 25.4 mm
Housing	Impact-modified thermoplastic
Top connection	360-degree swivel
Energy absorber	Integrated shock pack with fall-clearance charts
Service temperature	-40 to 130 F / -40 to 54 C
Cited compliance	ANSI Z359.14-2021; OSHA 1910.140 and 1926.502