Benecor Fleet XL Standard-Duty - 2,100-Gallon DEF Storage and Dispensing System

The Benecor Fleet XL Standard-Duty 2,100-gallon DEF system combines a fiberglass enclosure, stainless steel piping, 110% secondary containment and a half-horsepower submersible pump. The documented front-dispenser configuration has a 20-foot hose and automatic stainless steel nozzle; the hose reel belongs to the Standard-DutyPlus package.

Manufacturer Fleet XL Standard-Duty two-page specification linecard
Current manufacturer SD Series model and capacity table

Manufacturer	Benecor
Model	Fleet XL Standard-Duty 2100 G
Nominal DEF capacity	2,100 US gal
Documented configuration	Fleet XL Standard-Duty, front dispenser
Width	49.2 in.
Height	99.8 in.
Depth	191.5 in.
Secondary containment	110%
Enclosure	Fiberglass
Piping	Stainless steel
Pump	Benecor 1/2 HP DEF submersible
Delivery hose	20 ft
Nozzle	Automatic stainless steel with breakaway swivel
Pump control	Integrated nozzle-boot switch relay
Service access	Roof
Handling	Forklift accessible
Fill access	Lockable fill box
Overfill prevention	Stainless steel valve
Electrical panel/components	UL / cUL enclosed, as factory linecard describes
DEF standards	ISO 22241-3 and -4, manufacturer claim